





LABdex



-40°C Upright Freezer LX5020UF



Email: info@labdex.com **website:** www.labdex.com



Description

-40°C Upright Freezer LX5020UF offers an extensive storage capacity for various medical products. It has a slim and vertical structure to fit in constraint area. It is environmental friendly providing a temperature range from -30°C to -40°C with a stable performance. It is equipped with a highly efficient compressor. The condenser at the bottom ensures temperature stability and system reliability.

Specifications

Capacity	268 L
Shelf/drawer	Shelves
Cooling method	Direct cooling
Defrost	Manual
Refrigerant	R290
Noise	48 (db)
Ambient temperature	10~32 °C
Temperature range	-30~-40 °C
Compressor	CUBIGEL/1
Condenser	Wire tube
Sensor type	NTC
Temperature controller	Microprocessor
Display	Digital display
Inside material	Color sprayed steel
Outside material	Color sprayed steel
Insulation	PURF
Power consumption	4 (kWh/24h)
Power	300 W
Current	1.6A

Voltage/Frequency	220V/50Hz
Interior size (W x D x H)	508 x 455 x 1137 mm
Exterior size (W x D x H)	690 x 680 x 1635 mm
Package size (W x D x H)	760 x 760 x 1750 mm
Net weight	100 kgs
Gross weight	120 kgs

Features

- ~ Designed with microprocessor control system and LED display
- ~ CFC-free refrigerant and energy-saving
- ~ Audible and visual alarm
- ~ Door safety lock
- ~ It has manual defrost system
- ~ Inner door to avoid more cooling leaking out, and provide more stable inside temperature performance
- ~ Upright side door with build-in handle for easy opening

Applications

- ~ Used in medical, clinical, food industries, preservation, blood banks, pharmaceutical and in laboratories, etc.

Standard Accessories

- ~ Foot
- ~ Castor
- ~ Test hole
- ~ Remote alarm port



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com